

FEATURES

- High end aluminum heatsink with a unique elegant design
- Illuxtron patented optical lens system that makes pin-hole light possible
- Anti glare cap that ensures no stray light. The total light opening is only 8mm!

Bartenbach
lighting optics



With integrated PSU adapter, not visible after installation.

COLOURS

Available colours:



Nr	Housing	Ring
	RAL 9016	
XX=61	Matt white	Gold
XX=63	Matt white	Silver
XX=62	Matt white	Black
XX=65	Matt white	White
XX=52	Matt white	Beige
XX=53	Matt white	Bronze
XX=54	Matt white	Green



Nr	Housing	Ring
	RAL 9005	
XX=71	Matt black	Gold
XX=74	Matt black	Silver
XX=72	Matt black	Black
XX=76	Matt black	White
XX=70	Matt black	Beige
XX=78	Matt black	Bronze
XX=79	Matt black	Green


Pointer Spot Pendant 3F

Adjustable

SPECIFICATIONS

Beam angle (FWHM)	35° (45° FWTM) / 60° (80° FWTM)
Fixture material	Housing: Die cast aluminium
Environment	Indoor
IK rate	IK03
Operating temperature (Ta)	-20°C / +45°C 1
Safety marks	EN60598 / EN62031 / EN62471
EMC compliance	EN55015
Colour consistency (SDCM)	MacAdam step 3
Warranty	7 years * (within the European Union and the countries of the Free Trade Association for products delivered after 1 May 2015)
Energy class	These products contain a light source of energy efficiency class F (2700K/3000K) and class E (4000K)

This luminaire contains built-in LED lamps. There are no exchangeable parts inside the luminaire. EU 874/2012



POINTER SPOT PENDANT 3F (dimnable - incl. individual power supply)

CRI93 220-240V

ITEM SPECIFICATIONS (PART A)


Description	Item code	Input	W	Lm	Lm/W	CRI (typ.)	UGR	Pf	Ripple	Inrush current	B-16A Fuse
Pointer Spot Pendant 3F 35° 325 Lm 2700K CRI93 No dim	0Y3W03XXLU02	220-240V	9,4	325	35	93	8.3	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 35° 350 Lm 3000K CRI93 No dim	0Y3W03XXLV02	220-240V	9,4	350	37	93	8.5	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 35° 375 Lm 4000K CRI93 No dim	0Y3W03XXLW02	220-240V	9,4	375	40	93	8.8	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 60° 475 Lm 2700K CRI93 No dim	0Y3W03XXLX02	220-240V	9,4	475	51	93	19.5	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 60° 525 Lm 3000K CRI93 No dim	0Y3W03XXLY02	220-240V	9,4	525	56	93	19.9	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 60° 575 Lm 4000K CRI93 No dim	0Y3W03XXLZ02	220-240V	9,4	575	61	93	20,2	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 35° 325 Lm 2700K CRI93 Triac dim	0Y3W03XXLG02	220-240V	9,4	325	35	93	8.3	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 35° 350 Lm 3000K CRI93 Triac dim	0Y3W03XXLH02	220-240V	9,4	350	37	93	8.5	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 35° 375 Lm 4000K CRI93 Triac dim	0Y3W03XXLJ02	220-240V	9,4	375	40	93	8.8	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 60° 475 Lm 2700K CRI93 Triac dim	0Y3W03XXLK02	220-240V	9,4	475	51	93	19.5	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 60° 525 Lm 3000K CRI93 Triac dim	0Y3W03XXLL02	220-240V	9,4	525	56	93	19.9	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 60° 575 Lm 4000K CRI93 Triac dim	0Y3W03XXLM02	220-240V	9,4	575	61	93	20,2	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 35° 325 Lm 2700K CRI93 Dali	0Y3W03XXLO02	220-240V	9,4	325	35	93	8.3	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 35° 350 Lm 3000K CRI93 Dali	0Y3W03XXLI02	220-240V	9,4	350	37	93	8.5	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 35° 375 Lm 4000K CRI93 Dali	0Y3W03XXL202	220-240V	9,4	375	40	93	8.8	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 60° 475 Lm 2700K CRI93 Dali	0Y3W03XXL302	220-240V	9,4	475	51	93	19.5	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 60° 525 Lm 3000K CRI93 Dali	0Y3W03XXL402	220-240V	9,4	525	56	93	19.9	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 60° 575 Lm 4000K CRI93 Dali	0Y3W03XXL502	220-240V	9,4	575	61	93	20,2	0.97	<3%	5A 50μS	50 pcs

ITEM SPECIFICATIONS (PART B)

Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected Lifetime			Reported Lifetime*		
						L70B10	L80B10	L90B10	L70B10	L80B10	L90B10
Pointer Spot Pendant 3F LV 2700K CRI93 II	F	F	940 gr	310x180x60 mm	42 pcs	177.000 hrs	113.000 hrs	51.000 hrs	>102.000 hrs	>102.000 hrs	51.000 hrs
Pointer Spot Pendant 3F LV 3000K CRI93 II	F	F	940 gr	310x180x60 mm	42 pcs	177.000 hrs	113.000 hrs	51.000 hrs	>102.000 hrs	>102.000 hrs	51.000 hrs
Pointer Spot Pendant 3F LV 4000K CRI93 II	E	E	940 gr	310x180x60 mm	42 pcs	177.000 hrs	113.000 hrs	51.000 hrs	>102.000 hrs	>102.000 hrs	51.000 hrs


All values are measured at 230V (+/- 7%). *Based on 17.000hrs of LM80 testing at 700mA and a Tc85 °C.

DIMENSIONS



TRACKS

On request! Ask our sales department about the possibilities.



POINTER SPOT PENDANT 3F (dimnable - incl. individual power supply)

CRI82 220-240V

ITEM SPECIFICATIONS (PART A)


Description	Item code	Input	W	Lm	Lm/W	CRI (typ.)	UGR	Pf	Ripple	Inrush current	B-16A Fuse
Pointer Spot Pendant 3F 35° 500 Lm 2700K CRI82 No dim	0Y2703XXLU02	220-240V	9,2	500	54	82	8.5	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 35° 525 Lm 3000K CRI82 No dim	0Y2703XXLV02	220-240V	9,2	525	57	82	8.7	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 35° 550 Lm 4000K CRI82 No dim	0Y2703XXLW02	220-240V	9,2	550	60	82	8.8	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 60° 550 Lm 2700K CRI82 No dim	0Y2703XXLX02	220-240V	9,2	550	60	82	18.8	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 60° 600 Lm 3000K CRI82 No dim	0Y2703XXLY02	220-240V	9,2	600	65	82	19.1	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 60° 650 Lm 4000K CRI82 No dim	0Y2703XXLZ02	220-240V	9,2	650	71	82	19.4	0.95	<3%	7A 13μS	50 pcs
Pointer Spot Pendant 3F 35° 500 Lm 2700K CRI82 Triac dim	0Y2703XXLG02	220-240V	9,2	500	54	82	8.5	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 35° 525 Lm 3000K CRI82 Triac dim	0Y2703XXLH02	220-240V	9,2	525	57	82	8.7	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 35° 550 Lm 4000K CRI82 Triac dim	0Y2703XXLJ02	220-240V	9,2	550	60	82	8.8	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 60° 550 Lm 2700K CRI82 Triac dim	0Y2703XXLK02	220-240V	9,2	550	60	82	18.8	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 60° 600 Lm 3000K CRI82 Triac dim	0Y2703XXLL02	220-240V	9,2	600	65	82	19.1	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 60° 650 Lm 4000K CRI82 Triac dim	0Y2703XXLM02	220-240V	9,2	650	71	82	19.4	0.92	<5%	48A 50μS	20 pcs
Pointer Spot Pendant 3F 35° 500 Lm 2700K CRI82 Dali	0Y2703XXL002	220-240V	9,2	500	54	82	8.5	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 35° 525 Lm 3000K CRI82 Dali	0Y2703XXL102	220-240V	9,2	525	57	82	8.7	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 35° 550 Lm 4000K CRI82 Dali	0Y2703XXL202	220-240V	9,2	550	60	82	8.8	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 60° 550 Lm 2700K CRI82 Dali	0Y2703XXL302	220-240V	9,2	550	60	82	18.8	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 60° 600 Lm 3000K CRI82 Dali	0Y2703XXL402	220-240V	9,2	600	65	82	19.1	0.97	<3%	5A 50μS	50 pcs
Pointer Spot Pendant 3F 60° 650 Lm 4000K CRI82 Dali	0Y2703XXL502	220-240V	9,2	650	71	82	19.4	0.97	<3%	5A 50μS	50 pcs

ITEM SPECIFICATIONS (PART B)

Description	Safety class	Energy class	Weight	Dimensions single carton	Quantity per carton	Expected Lifetime B10 reported (25°C)		
						L70B10	L80B10	L90B10
Pointer Spot Pendant 3F 2700K CRI82	I	F	940 gr	310x180x60 mm	42 pcs	>60.000 hrs	>60.000 hrs	>60.000 hrs
Pointer Spot Pendant 3F 3000K CRI82	I	F	940 gr	310x180x60 mm	42 pcs	>60.000 hrs	>60.000 hrs	>60.000 hrs
Pointer Spot Pendant 3F 4000K CRI82	I	E	940 gr	310x180x60 mm	42 pcs	>60.000 hrs	>60.000 hrs	>60.000 hrs

All values are measured at 230V (+/- 7%)

DIMENSIONS



TRACKS

On request! Ask our sales department about the possibilities.

